


Products Parameters

	Parameters	Standard ZS-H150	Cold Chain ZS-H150C	Ultra-thin ZS-H125	Heavy-load ZS-L2000	Customized ZS-X1
						
Basic	Dimensions	1076*940*150mm	1076*940*150mm	1106*940*125mm	1090*980*150mm	1.Customized Model for Different Environments: Low temperature, high temperature, dusty, explosion-proof, etc.Customized models for severe scenes 2.Customized Loads: Customized models for extended, widened, ultra narrow and surcharge load types 3.Customized Battery Capacity Battery customization options include larger capacity and extended operating time 4.Entire product line allows for secure communication and remote emergency stop, and meets PLd safety requirements. All models customizable in CE and UL versions.
	Applicable Pallet	1100≤ W ≤1500 mm 1000≤ D ≤1300 mm	1100≤ W ≤1500 mm 1000≤ D ≤1300 mm	1100≤ W ≤1500 mm 1000≤ D ≤1300 mm	1200≤ W ≤1500 mm 1000≤ D ≤1300 mm	
	Weight	350 kg	350 kg	300 kg	375 kg	
	Rated Load	1600 kg	1600 kg	1500 kg	2000 kg	
Performance	Operating Speed	1.5 ~ 2.0 m/s	1.5 ~ 2.0 m/s	1.5 ~ 2.0 m/s	0.8 ~ 1.0 m/s	
	Reversal Time	2.5 s	2.5 s	2.5 s	2.5 s	
	Accuracy of Positioning	±2 mm	±2 mm	±2 mm	±2 mm	
Battery	Battery Capacity	40 Ah	40 Ah/50 Ah	50 Ah	40 Ah	
	Charge Time	1 ~ 2 h	1 ~ 2 h	1 ~ 2 h	1 ~ 2 h	
	Battery	Lithium Iron Phosphate	Lithium Iron Phosphate	Lithium Iron Phosphate	Lithium Iron Phosphate	
	Battery Life	6 ~ 8 h	6 ~ 8 h/8 ~10 h	8 ~ 10 h	6 ~ 8 h	
Environmental	Applicable Temperature	-10℃ ~ 45℃	-25℃ ~ 0℃	-10℃ ~ 45℃	-10℃ ~ 45℃	